



FEATURES

- Fleck 9000 nickel plated alternating control valve
- Independently operated inlet/outlet bypass valve
- 3/4" FNPT stainless steel yoke connection
- 1" FNPT stainless steel yoke connection (optional)
- Features Enpress® Vortech™ distributor plate
- Garnet sand underbed to minimize pressure loss
- Standard brine safety float assembly and overflow fitting
- Standard salt grid plate
- Poly wound mineral tanks
- Includes Res-up feeder

General Specifications	ATI32	ATI48	ATI64	ATI96
	Grains Capacity / Regeneration	35,000	52,500	70,000
	32,000	48,000	64,000	96,000
	26,500	39,750	53,000	85,000
Salt Used / Regeneration (pounds per tank)	15.0	22.5	30.0	45.0
	10.0	15.0	20.0	25.0
	6.0	9.0	12.0	18.0
Maximum Raw Water Hardness (grains)	75	100	100	100
Maximum Clear Iron / Manganese (ppm)	15	20	20	20
Exchange Resin (cu. ft.) (per tank)	1.0	1.5	2.0	3.0
Garnet Sand Underbed (per tank)	15 lbs.	15 lbs.	35 lbs.	35 lbs.
Brine Tank (polyethylene with grid & safety)	18x33	18x33	18x33	18x40
Service Flow Rate (gpm per active tank)*	10.0	11.0	12.0	14.0
Backwash Flow Rate (gpm)	1.2	1.5	2.4	3.0
Gallons Used / Regeneration	59	68	102	135
Space Required (DxWxH inches)	18x34x56	18x36x62	18x38x56	18x42x73
Approximate Shipping Weight (pounds)	199	267	369	582

* The pressure drop does not exceed 15.0 psi at the service flow rate.