



FEATURES

- Perfect for Filtering and Softening in ONE system
- Features Enpress® Vortech™ mid plate technology
- *Signature Series*™ timeclock or meter initiated controls
- Advanced Electronic Technology & Simple programming
- Adjustable cycle times
- Calendar Day Override (metered versions only)
- Battery Back-Up
- Independently operated inlet/outlet bypass valve
- 3/4" FNPT stainless steel yoke connection
- 1" FNPT stainless steel yoke connection (optional)
- High Flow 1" distributor tube
- High capacity cation exchange resin
- Dome fill opening for ease of service
- High Flow brine safety float assembly, overflow fitting, grid plate, and brine well
- Other valve options available at an additional cost
- For Filter Media Options see Filter Media Guide (pg. 28)

General Specifications	Two Tanks in One			
	TSF32-10D	MSF32-10D	TSF48-15D	MSF48-15D
Regeneration Type	Timed	Metered	Timed	Metered
Filter Media Capacity	1 cu ft	1 cu ft	1.5 cu ft	1.5 cu ft
Softening Capacity	1 cu ft	1 cu ft	1.5 cu ft	1.5 cu ft
Service Flow Rate (gpm)*	5	5	8	8
Intermittent Flow Rate (gpm)	7	7	10	10
Backwash Flow Rate (gpm)	5	5	7	7
Mineral Tank Size (inches)	10x65	10x65	13x65	13x65
Gallons Used / Backwash	130	130	170	170
Space Required (DxWxH inches)	18x28x73	18x28x73	18x31x73	18x31x73
Approximate Shipping Weight (pounds)	126	126	182	182

* The pressure drop does not exceed 15.0 psi at the service flow rate.