

Filter Media Selection Guide		
Media	Description	Handles
Neutralizer	Granular / White / Sacrificial to water with pH < 7.0 / Max pH correction to 7.2 / Lowest pH application 5.8 / Must be replenished about every 3-6 months	Sediment (downflow) pH Correction
Corosex™	Semi-round / Off-White / Magnesium Oxide / Extremely reactive to pH dissolving rapidly adding alkalinity / 30% Corosex™ - 70% Neutralizer is best blend for correcting low pH / Will raise pH from lows around 5.0 to as high as 9.0+ / Must be replenished frequently / Consult factory with specific application questions	Sediment (downflow) pH Correction
Neu-Cor™	70% neutralizer / 30% Corosex™ mix. Sacrificial to water with any pH / max pH correction determined by contact time used for correction of extremely low pH down to 5.0 / Must be replenished every 3-6 months.	Sediment (downflow) pH correction
Granular Activated Carbon	Granular / Black / Wide application for removal of organics and some inorganics / Must be replaced on a regular basis / Life expectancy varies based on use	Sediment (downflow) Taste / Odor / Color Chlorine / Iodine
Birm™	Granular / Gray / Must not be used on waters with a pH < 6.8 / Must have dissolved oxygen present at a level of at least 15% of Iron & Manganese ppm / Max Iron & Manganese level 10ppm / Estimated life about 8-10 years	Sediment Iron (clear & red) Manganese (clear & red)
Filter Ag™	Granular / Off-White / Wide application for removal of sediment / Life expectancy is unlimited	Sediment
REACTR™ Blend	Granular / White-Black / Blend of Neutralizer, Filter Ag & Birm / Max life expectancy about 8-10 years but is dependent upon pH	Sediment Iron (clear & red) Manganese (clear & red) Sulfur Particles
ChemSorb™ Media	Granular / Light Greenish Color / Removes sediment down to 5 microns in size / Life expectancy is unlimited	Fine Sediment (Down to 5 microns)
"D" Gravel	Semi-Round / Brown / #20 Flint / Used as underbed for all media in all filters providing for excellent flow distribution in both service and backwash modes / Permanent unless fouled but can be cleaned and reused	Underbed

Filter media and gravel is shipped in convenient reusable buckets.

