



FEATURES

- *Signature Series™* control valve
- Advanced Electronic Technology & Simple programming
- Adjustable cycles
- Battery Back-Up
- High backwash flow capability
- Independently operated inlet/outlet bypass valve
- 3/4" FNPT stainless steel yoke connection
- 1" FNPT stainless steel yoke connection (optional)
- High Flow 1" distributor tube
- Poly wound mineral tank
- Includes KMNO₄ feed pot with grid platform and float shutoff
- Other valve options available at an additional cost

General Specifications				
	IF10	IF15	IF20	IF25
Filter Media	MTM™ Media			
Filter Media Capacity (cu ft)	1.00	1.50	2.00	2.50
Underbed "D" Gravel Required (pounds)	20	20	50	50
Mineral Tank (polyglass)	9x48	10x54	13x48	13x54
Potassium Permanganate Solution Tank Size	10x16			
Removal Capacities Iron / Sulfur	10 ppm / 3 ppm	10 ppm / 3 ppm	10 ppm / 3 ppm	10 ppm / 3 ppm
Service Flow Rate - Continuous (gpm)	4	5	6	8
Service Flow Rate - Intermittent (gpm)	6	7	8	10
Backwash Flow Rate (gpm)	5.0	5.0	7.0	7.0
Gallons Used / Regeneration	128	130	193	193
Space Required (DxWxH inches)	9x21x57	10x22x62	13x23x62	13x23x62
Approximate Shipping Weight (pounds)	82	102	125	170

Note: Caution should always be used in sizing filters! Always choose a unit by first satisfying the *Backwash requirement*. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions.