



Ideal for - Apartments, Factories, Farms, Hospitals, Laundries, Offices, Churches, Large Homes, Mobile Home Parks, Nursing Homes, Restaurants and Schools

These economical filters are designed to treat some of the most common undesirable water characteristics :

- Bad tastes, odors and colors, which can result from chlorine, decayed vegetation or volatile organic compounds (VOC's).
- Acidic water, which can corrode piping and equipment, resulting in property damage from leaks and broken pipes.

Media	Application	Comments
Carbon	Chlorine, VOC, Taste, Odor and Color	Periodic replacement of carbon will be required. Carbon life is dependent upon water quality and usage. (Normally 1 to 2 years for most city waters.)
Neutralizer	Acid Water (Down to 5.8 pH)	Periodic replenishing of media will be required. (Normally every 6 to 12 months depending on pH and water usage.)

- Water flows up through media, allowing for uniform contact.
- Because of upflow design, the need for backwash is eliminated!
- Maximum temperature is 120° F. Maximum pressure is 125 psi.
- These units **do not** remove turbidity and suspended solids. Refer to Commercial Water Filter Series if your water contains filterable solids, dirt, etc.

Filter Type	Model No.	Service GPM (at PSI Loss)	Pipe Size NPT	Media cu. ft.	Tank Size Dia. x Ht.	Overall Height	Shipping Weight (lbs.)
	DE-CHLORINATION ORGANIC REMOVAL						
Taste & Odor (Activated Carbon)	CU40C-10	14 (6) 7 (3)	1"	4	16" x 65"	70"	240
	CU50C-10	18 (11) 9 (5)	1"	5	18" x 65"	71"	330
	CU70C-10	16 (8) 12 (5)	1"	7	21" x 62"	71"	402
	CU70C-20	24 (3) 12 (2)	2"	7	21" x 62"	88"	404
	CU100C-10	17 (8) 15 (7)	1"	10	24" x 72"	79"	560
	CU100C-20	31 (3) 16 (2)	2"	10	24" x 72"	92"	562
	CU140C-20	50 (4) 25 (2)	2"	14	30" x 72"	92"	890
	CU180C-20	70 (5) 35 (3)	2"	18	36" x 72"	92"	1,356
Neutralizer (Calcite)	CU40N-10	11 (5)	1"	4	16" x 65"	70"	488
	CU50N-10	15 (9)	1"	5	18" x 65"	71"	640
	CU70N-10	16 (8)	1"	7	21" x 62"	71"	836
	CU70N-20	19 (2)	2"	7	21" x 62"	88"	838
	CU100N-10	17 (8)	1"	10	24" x 72"	79"	1,180
	CU100N-20	25 (2)	2"	10	24" x 72"	92"	1,182
	CU140N-20	39 (3)	2"	14	30" x 72"	92"	1,758
	CU180N-20	56 (4)	2"	18	36" x 72"	92"	2,472

- Intermittent flow rates and / or favorable local conditions may allow higher flow rates.
- Larger Units are available.
- Individual spec drawings are available for all models listed.

Please contact factory